

# V Series Crystal



- 5.0mm x 3.2mm x 1.2mm 2 Pads Ceramic Package
- RoHS Compliant
- Rugged AT-cut Crystal Construction
- Tape and Reel Packaging Available



Frequency Range	12.000 MHz to 50.000 MHz
Frequency Tolerance / Stability	(See Part Number Guide for Options)
Operable Temperature	(See Part Number Guide for Options)
Storage Temperature	-40°C to +85°C
Aging	±5 ppm per year
Shunt Capacitance	5 pF
Load Capacitance	(See Part Number Guide for Options)
Oscillation Mode	Fundamental
Drive Level	10µW typ / 300 max
Insulation Resistance	500 M Ohms / 100 VDC
Shock	MIL-STD-883, Meth 2002, Cond B
Solderability	MIL-STD-883, Meth 2003
Solvent Resistance	MIL-STD-202, Meth 215
Vibration	MIL-STD-883, Meth 2007, Cond A
Gross Leak Test	MIL-STD-883, Meth 1014, Cond C
Fine Leak Test	MIL-STD-883, Meth 1014, Cond A

## Environmental & Mechanical Detail

Shock	MIL-STD-883, Method 2002 Cond B
Solderability	MIL-STD-883, Method 2003
Solvent Resistance	MIL-STD-202, Method 215
Vibration	MIL-STD-883, Method 2007, Cond A
Gross Leak Test	MIL-STD-883, Method 1014, Cond C
Fine Leak Test	MIL-STD-883, Method 1014, Cond A2
MSL	Level 1 per IPC/JEDEC J-STD 20

## Marking Detail

Line 1: MXX.XXX
XX.XXX = Frequency in MHz
Line 2: SYMCL
S = Internal Code
YM = Date Code (Year/Month)
CC = Crystal Parameters Code
L = Denotes RoHS Compliant



MMD Monitor/Quartztek  
 30400 Esperanza, Rancho Santa Margarita, CA, 92688  
 Phone: (949) 709-5075, Fax: (949) 709-3536, [www.mmdcomp.com](http://www.mmdcomp.com)  
 Sales@mmdcomp.com



Revision:	V091310 D
-----------	-----------

